



Details

- similar in function to Open Top Containers
- specially designed to transport heavy cargo that is best loaded by crane and cargo that extends out of the top of the container
- equipped with a removable steel roof
- if the cargo protrudes out of the container, the roof can be removed and attached to the inside of the container
- this allows the container to be reused to carry general cargo on a possible return trip and thus reduce the cost of empty positioning
- goods can best be secured to the interior lashing points located in the vicinity of the side walls only when the roof is on
- some models also have a swinging header (rear top rail) to facilitate easier loading operations
- roof opening can vary depending on the model (one or more pieces)

Outside dimensions

length	mm	6058
	ft	19' 10 1/2"
width	mm	2438
	ft	8'
height	mm	2591
	ft	8' 6"

Roof opening

width	mm	5590
	ft	18' 4"
height	mm	2208
	ft	7' 2 7/8"

Inside dimensions

length	mm	5886
	ft	19' 3 3/4"
width	mm	2342
	ft	7' 8 1/8"
height	mm	2313
	ft	7' 7"
capacity	cbm	32.8
	cbft	1160

Weights

Tare	kg	2700
	pd	5950
Max. payload	kg	27780
	pd	61250
Max. Gross	kg	30480
	pd	67200

Door opening

width	mm	2336
	ft	7' 8"
height	mm	2276
	ft	7' 5 5/8"
width side door	mm	./.
	ft	./.
height side door	mm	./.
	ft	./.

Certification

ISO size type	22U6
ISO size group	22UT