



Details

- similar in function to Open Top Containers
- specially designed to transport heavy cargo that is best loaded by crane and cargo that extends out of the top of the container
- equipped with a removable steel roof
- if the cargo protrudes out of the container, the roof can be removed and attached to the inside of the container
- this allows the container to be reused to carry general cargo on a possible return trip and thus reduce the cost of empty positioning
- goods can best be secured to the interior lashing points located in the vicinity of the side walls only when the roof is on
- some models also have a swinging header (rear top rail) to facilitate easier loading operations
- roof opening can vary depending on the model (one or more pieces)

Outside dimensions

length	mm	12192
	ft	40'
width	mm	2438
	ft	8'
height	mm	2591
	ft	8' 6"

Roof opening

width	mm	11724
	ft	38' 5 1/2"
height	mm	2208
	ft	7' 2 7/8"

Inside dimensions

length	mm	12020
	ft	36' 5 1/4"
width	mm	2342
	ft	7' 8 1/8"
height	mm	2313
	ft	7' 7"
capacity	cbm	67.2
	cbft	2374

Weights

Tare	kg	4700
	pd	10360
Max. payload	kg	25780
	pd	56840
Max. Gross	kg	30480
	pd	67200

Door opening

width	mm	2336
	ft	7' 8"
height	mm	2292
	ft	7' 6 1/4"
width side door	mm	./.
	ft	./.
height side door	mm	./.
	ft	./.

Certification

ISO size type	42U6
ISO size group	42UT