



Details

- used for temperature-sensitive goods
- insulated panels, roof and doors
- does not have a built in refrigeration unit
- can not heat or cool themselves but retain the temperature of the cargo for a specific length of time
- approximately 30 cm higher than normal Insulated Containers
- attention must be paid to any height restrictions such as bridge and tunnel height when using road or rail
- may require the need to use a special chassis or wagon

Outside dimensions

length	mm	12192
	ft	40'
width	mm	2438
	ft	8'
height	mm	2896
	ft	9' 6"

Roof opening

width	mm	./.
	ft	./.
height	mm	./.
	ft	./.

Inside dimensions

length	mm	11958
	ft	39' 2 25/32"
width	mm	2254
	ft	7' 4 47/64"
height	mm	2545
	ft	8' 4 13/16"
capacity	cbm	68.6
	cbft	2424

Weights

Tare	kg	4400
	pd	9400
Max. payload	kg	29600
	pd	65560
Max. Gross	kg	34000
	pd	74960

Door opening

width	mm	2292
	ft	7' 6 15/64"
height	mm	2556
	ft	8' 4 5/8"
width side door	mm	./.
	ft	./.
height side door	mm	./.
	ft	./.

Certification

ISO size type	45H5
ISO size group	45HI