



Details

- suitable for transport and storage
- fitted with an electric or diesel cooling / heating unit
- insulated panels, roof and doors
- able to maintain temperatures ranging from -25°C to +30°C in conditions whereby the ambient outside
- temperature can be up to +50°C
- approximately 30 cm higher than normal Reefers
- attention must be paid to any height restrictions such as bridge and tunnel height when using road or rail
- may require the need to use a special chassis or wagon

Outside dimensions

length	mm	12192
	ft	40'
width	mm	2438
	ft	8'
height	mm	2896
	ft	9' 6"

Roof opening

width	mm	./.
	ft	./.
height	mm	./.
	ft	./.

Inside dimensions

length	mm	11643
	ft	38' 2"
width	mm	2288
	ft	7' 6 1/8"
height	mm	2498
	ft	8' 2 3/8"
capacity	cbm	66.5
	cbft	2348

Weights

Tare	kg	4180
	pd	9220
Max. payload	kg	26300
	pd	57980
Max. Gross	kg	30480
	pd	67200

Door opening

width	mm	2288
	ft	7' 6 1/8"
height	mm	2517
	ft	8' 3 1/8"
width side door	mm	./.
	ft	./.
height side door	mm	./.
	ft	./.

Certification

ISO size type	45R1
ISO size group	45RT